

76-80 Lipton Drive Thomastown 3074

Telephone: (03) 9462 3730

Fax: (03) 9460 5230

Mobile: 0431 481 661

## **BONDTECH N93L ADHESIVE**

### **TECHNICAL DATA SHEET**

#### **DESCRIPTION & USES:**

Bondtech N93L is low viscosity, brush or scraper grade solvent based contact adhesive. Its uses include fixing vinyl skirting to plaster, timber and metal substrates.

#### **METHOD OF APPLICATION:**

1. To obtain the best results, the materials to be bonded should be dry, clean and free from dust, grit, oil, grease and other contaminants.
2. Apply an even coat of adhesive to both surfaces by brush or scraper. On porous surfaces a second application may be required.
3. Allow solvent to evaporate and adhesive to become tacky. Place the surfaces together making sure that they are correctly positioned beforehand as no adjustment is possible after the surface has met.
4. Press both surfaces together; making sure sufficient pressure is applied to bring both surfaces into close contact.

#### **PROPERTIES:**

- Appearance: Light yellow liquid.
- Viscosity: Brush or scraper grade liquid.
- Coverage: 3 - 4m<sup>2</sup> per litre.

#### **CLEAN UP:**

- Using N or NC Solvent.

**Note: Additional information on physical properties, health hazards, storage, handling and transport is available in the Material Safety Data Sheet (MSDS).**